Stainless Steel Screw Pin Shackles




Fehr Bros. Industries, Inc. WWW.FEHR.COM 800-431-3095

Fehr Brothers offers a variety of long lasting and robustly designed Anchor Shackles to meet your individual needs including load rated anchor shackles, safety shackles, commercial shackles, and a range of stainless steel shackles.

The screw pin allows for easy attachment and detachment with a hole in the pin for securement. Our anchor shackles form an integral part for many applications including industrial, agriculture and marine rigging systems.

Quality Matters!


Type 316 Stainless Steel



Fehr Stainless Steel Screw Pin Bow Shackle Type 316 Stainless Steel												
Part #	Size (in.)	Working Load Limit (Ibs.)	Weight (Ibs.)/Each	Dimensions (in.)								
				A (Pin Diameter)	В	С	D	E				
SSPA187	3/16"	660	.04	.187	.40	1.50	1.00	.189				
SSPA250	1/4"	930	.06	.250	.50	1.80	1.20	.224				
SSPA312	5/16"	1,375	.16	.312	.70	2.25	1.45	.307				
SSPA375	3/8"	2,365	.31	.375	.84	2.75	1.83	.363				
SSPA500	1/2"	3,400	.66	.500	1.00	3.40	2.30	.46				
SSPA625	5/8"	5,500	1.44	.625	1.26	4.45	2.85	.59				
SSPA750	3/4"	7,700	2.25	.750	1.39	5.10	3.34	.71				
SSPA875	7/8"	8,000	2.90	.875	1.64	5.85	3.70	.875				
SSPA100	1"	10,000	4.67	.925	1.965	6.625	4.16	.925				

Stainless Steel Wide 'D' Shackle												
Туре 316												
Part #	Size (in.)	Working Load Limit (Ibs.)		Dimensions (in.)								
			Weight (Ibs.)/Each	A (Pin Diameter)	В	С	D					
SSDS312	5/16"	1,300	.14	.312	.315	1.12	1.20					
SSDS375	3/8"	1,500	.34	.375	.394	1.625	2.15					
SSDS500	1⁄2″	2,200	.60	.500	.472	1.88	2.60					

Working Load Limit is the maximum working load which should ever be applied to the product under any condition. The Working Load Limit is based on a load being uniformly applied in a straight line pull. Inspect regularly. Replace if nicked, worn or damaged. Avoid shock loads. Use only Duty Rated Shackles, with embossed WLL, for overhead lifting.



Type 316 Straight 'D' Shackles Available

www.fehr.com (800) 431-3095 fax (845) 246-3330